

**WHAT IS CLAIMED IS:**

1. A method of generating interrupts of a network interface card which transceives data, the method comprising:

(a) receiving data frames;

5 (b) estimating a first time delay and a second time delay in response to a received data frame and counting a number of received data frames;

(c) determining whether the first time delay has passed and generating an interrupt if the first time delay has passed;

10 (d) counting the number of data frames if the first time delay has not passed and generating the interrupt if the number of data frames equals N;

(e) determining whether the second time delay has passed if the number of data frames is not equal to N and generating the interrupt if the second time delay has passed, or going back to step (b) if the second time delay has not passed;

15 (f) stopping operations of estimating the first and second time delays and counting the number of data frames in response to the interrupts generated, and transmitting the received data frames; and

(g) receiving a new data frame and going back to step (b).

20 2. The method of claim 1, wherein the first time delay starts from when a first data frame is received.

3. The method of claim 1, wherein the second time delay is a time interval between received data frames and is shorter than the first time delay.

25

4. A method of generating interrupts of a network interface card which transceives data, the method comprising:

(a) receiving data frames;

30 (b) estimating a packet time delay in response to the received data frames;

(c) determining whether the packet time delay has passed and generating

an interrupt if the packet time delay has passed, or going back step (b) if the packet time delay has not passed;

(d) stopping an operation of estimating the packet time delay and transmitting the received data frames; and

5 (e) receiving a new data frame and going back to step (b).

5. The method of claim 5, wherein the packet time delay is a time interval between received data frames.

10 6. A method of generating interrupts of a network interface card which transceives data, the method comprising:

(a) receiving data frames;

(b) estimating a first time delay in response to the received data frames, counting a number of received data frames, and recognizing a type field of the received data frames;

15 (c) determining whether the first time delay has passed and generating an interrupt if the first time delay has passed;

(d) counting the number of received data frames and generating the interrupt if the number of received data frames is N;

20 (e) determining whether a type field is identical to a predetermined type field if the number of data frames is not equal to N, generating the interrupt if the type field is identical to the predetermined type field, or going back to step (b) if the type field is not identical to the predetermined type field;

25 (f) stopping operations of estimating the first time delay, counting the number of received data frames and recognizing the type field of the data frame in response to the interrupt generated, and transmitting the received data frames; and

(g) receiving a new data frame and going back to step (b).

30 7. The method of claim 6, wherein the first time delay starts from when the first data frame is received.

8. A method of generating interrupts of a network interface card which transceives data, the method comprising:

(a) receiving data frames;

(b) recognizing a type field of the received data frames;

5 (c) determining whether the type field of the received data frames is identical to a predetermined type field and generating an interrupt if the type field is identical to the predetermined type field or going back to step (b) if the type field is not identical to the predetermined type field;

(d) stopping an operation of recognizing the type field of the received data frames in response to the generated interrupt and transmitting the received data frames; and

(e) receiving a new data frame and going back to step (b).

15 9. A method of generating interrupts of a network interface card which transceives data, the method comprising:

(a) receiving data frames;

(b) estimating a first time delay in response to the received data frames, counting a number of received data frames, and recognizing a protocol field of a packet header in a data field of the received data frames;

20 (c) determining whether the first time delay has passed and generating an interrupt if the first time delay has passed;

(d) determining whether the number of received data frames is equal to N if the first time delay has not passed and generating the interrupt if the number of data frames is equal to N;

25 (e) determining whether the protocol field is identical to a predetermined protocol field if the number of received data frames is not equal to N, generating the interrupt if the protocol field is identical to the predetermined protocol field, or going back to step (b) if the protocol field is not identical to the predetermined protocol field;

30

(f) stopping operations of estimating the first time delay, counting the number of received data frames and recognizing the protocol field in response to the generated interrupts, and transmitting the received data frames; and  
(g) receiving a new data frame and going back to step (b).

5

10. The method of claim of claim 9, wherein the first time delay starts from when a first data frame is received.

11. A method of generating interrupts of a network interface card which transceives data, the method comprising:

10

(a) receiving data frames;

(b) recognizing a protocol field of a packet header in a data field of the received data frames;

15

(c) determining whether the protocol field is identical to a predetermined protocol field and generating an interrupt if the protocol field is identical to the predetermined protocol field, or going back to step (b) if the protocol field is not identical to the predetermined protocol field;

(d) stopping an operation of recognizing the protocol field and transmitting the received data frames; and

20

(e) receiving a new data frame and going back to step (b).

12. A method of generating interrupts of a network interface card which transceives data, the method comprising:

(a) receiving data frames;

25

(b) estimating a first time delay and a second time delay in response to the received data frames, counting a number of received data frames, recognizing a type field of the received data frames, and recognizing a protocol field of a packet header in a data field of the received data frames;

30

(c) determining whether the first time delay has passed and generating an interrupt if the first time delay has passed;

(d) counting the number of received data frames if the first time delay has not passed and generating the interrupt if the number of received data frames is equal to N;

(e) determining whether the second time delay has passed if the number of received data frames is not equal to N and generating the interrupt if the second time delay has passed;

(f) determining whether a type field is identical to a predetermined type field if the second time delay has not passed and generating the interrupt if the type field is identical to the predetermined type field;

(g) determining whether the protocol field of the received data frames is identical to a predetermined protocol field if the type field is not identical to the predetermined type field and generating the interrupt if the protocol field is identical to the predetermined protocol field, or going back to step (b) if the protocol field is not identical to the predetermined protocol field;

(h) stopping operations of estimating the first time delay and the second time delay, counting the number of received data frames and recognizing the type field and the protocol field of the data frames in response to the generated interrupt, and transmitting the received data frames; and

(i) receiving a new data frame and going back to step (b).

13. The method of claim 12, wherein the first time delay starts from when a first data frame is received.

14. The method of claim 12, wherein the second time delay is a time interval between the received data frames and is shorter than the first time delay.

15. A network interface card, which minimizes the number of times where interrupts are generated, the network interface card comprises:

a first time delay estimating circuit, which estimates a first time delay in response to received data frames and stops estimating the first time delay in response to an interrupt;

a second time delay estimating circuit, which estimates a second time delay in response to the received data frames and stops estimating the second time delay in response to the interrupt;

5 a data frame counting circuit, which counts a number of received data frames in response to the received data frames and stops counting the data frames in response to the interrupt;

10 a determining circuit which determines whether the time reaches the first time delay in response to an output signal of the first time delay estimating circuit, determines whether the time reaches the second time delay in response to an output signal of the second time delay estimating circuit, determines whether the number of received data frames is equal to N in response to an output signal of the data frame counting circuit, and generates an interrupt control signal for controlling generation of the interrupt; and

15 an interrupt generating circuit which generates the interrupt in response to the interrupt control signal.

16. The network interface card of claim 15, wherein the first time delay is estimated from when a first data frame is received.

20 17. The network interface card of claim 15, wherein the second time delay is a time interval between the received data frames and is shorter than the first time delay.

25 18. A network interface card, which minimizes the number of times where interrupts are generated, the network interface card comprises:

a first time delay estimating circuit, which estimates a first time delay in response to received data frames and stops estimating the first time delay in response to an interrupt;

30 a type recognizing circuit, which recognizes a type field of data, frames in response to the received data frames and stops recognizing the type field in response to the interrupt;

a data frame counting circuit, which counts a number of received data frames in response to the received data frames and stops counting the number of received data frames in response to the interrupt;

5 a determining circuit which determines whether the first time delay estimating circuit reaches a time delay in response to the output signal of the first time delay estimating circuit, determines whether the number of received data frames is equal to N in response to an output signal of the data frame counting circuit, determines whether the type field recognized in response to an output signal of the type recognizing circuit is identical to a predetermined type field, and  
10 generates an interrupt control signal for controlling generation of the interrupt; and

an interrupt generating circuit which generates the interrupt in response to the interrupt control signal.

15 19. The network interface card of claim 18, wherein the first time delay starts from when a first data frame is received.

20. A network interface card, which minimizes the number of times where interrupts are generated, the network interface card comprises:

20 a first time delay estimating circuit, which estimates a first time delay in response to received data frames and stops estimating the first time delay in response to an interrupt;

a protocol recognizing circuit which recognizes a protocol field of a packet header in a data field of the received data frames in response to the received data frames and stops recognizing the protocol field in response to the interrupt;

25 a data frame counting circuit, which counts a number of received data frames in response to the received data frames and stops counting the number of received data frames in response to the interrupt;

30 a determining circuit which determines whether the first time delay estimating circuit reaches a time delay in response to the output signal of the first time delay estimating circuit, determines whether the number of received data

frames is equal to N in response to an output signal of the data frame counting circuit, determines whether the protocol field recognized in response to an output signal of the type recognizing circuit is identical to a predetermined type field, and generates an interrupt control signal for controlling generation of the interrupt;  
5 and

an interrupt generating circuit which generates the interrupt in response to the interrupt control signal.

21. The method of claim 18, the first time delay is estimated from when  
10 a first data frame is received.

22. A network interface card, which minimizes the number of times where interrupts are generated, the network interface card comprises:

a first time delay estimating circuit, which estimates a first time delay in  
15 response to received data frames and stops estimating the first time delay in response to an interrupt;

a second time delay estimating circuit, which estimates a second time delay in response to the received data frames and stops estimating the second time delay in response to the interrupt;

a type recognizing circuit, which recognizes a type field of data, frames in  
20 response to the received data frames and stops recognizing the type field in response to the interrupt;

a data frame counting circuit, which counts a number of received data, frames in response to the received data frames and stops counting the number  
25 of received data frames in response to the interrupt;

a protocol recognizing circuit which recognizes a protocol field of a packet header in a data field of the received data frames in response to the received data frames and stops recognizing the protocol field in response to the interrupt;

a determining circuit which determines whether the first time delay has  
30 passed in response to the output signal of the first time delay estimating circuit, determines whether the second time delay has passed in response to an output

signal of the second time delay estimating circuit, determines whether the type field recognized in response to an output signal of the type recognizing circuit is identical to a predetermined type field, determines whether the number of received data frames is equal to N in response to an output signal of the data frame counting circuit, determines whether the protocol field recognized by the protocol recognizing circuit in response to an output signal of the protocol recognizing circuit and generates an interrupt control signal for controlling generation of the interrupt; and  
an interrupt generating circuit which generates the interrupt in response to the interrupt control signal.

23. The network interface card of claim 22, wherein the first time delay starts from when a first data frame is received.

24. The network interface card of claim 22, wherein the second time delay is a time interval between the received data frames and is shorter than the first time delay.

25. The network interface card of claim 15, the network interface card further comprises:

a receiving circuit which receives data frames and transmits the received data frames to the first time delay estimating circuit, the second time delay circuit, and the data frame counting circuit; and

a transmitting circuit which receives and transmits the interrupt.

25

26. The network interface card of claim 18, the network interface card further comprises:

a receiving circuit which receives data frames and transmits the received data frames to the first time delay estimating circuit, the data frame counting circuit, and the type recognizing circuit; and

30

a transmitting circuit which receives and transmits the interrupt.

27. The network interface card of claim 20, the network interface card further comprises:

a receiving circuit which receives data frames and transmits the received data frames to the first time delay estimating circuit, the data frame counting circuit, and the protocol recognizing circuit; and

a transmitting circuit which receives and transmits the interrupt.

28. The network interface card of claim 22, the network interface card further comprises:

a receiving circuit which receives data frames and transmits the received data frames to the first time delay estimating circuit, the second time delay circuit, the data frame counting circuit, the type recognizing circuit, and the protocol recognizing circuit; and

a transmitting circuit which receives and transmits the interrupt.